

# PRODUCT DATA SHEET



## PAO-GEAR Food Grade 150

*FG*  
*FOOD GRADE*

### Synthetic Gear Lubricant

PAO-GEAR Food Grade - is a full synthetic hydrocarbon (PAO) based gear lubricant with an additive blend that includes oxidization inhibitors, anti-wear and extreme pressure (EP) elements that extend the service life of the lubricant and enable it to meet the highest level of the FZG gear wear test.

PAO-GEAR Food Grade was developed specifically to meet the rigors of the baking, meat and poultry processing, bottling canning, dairy and packaging industries.

Available in viscosities from 150 to 680, PAO-GEAR Food Grade is suitable for gearboxes and drives in production machinery, power transmission systems, and other applications.

PAO-GEAR Food Grade meets FDA requirements for use where incidental contact with food is possible and is NSF Registered, H1.

Properties / Characteristics	PAO-GEAR Food Grade 150
ISO Grade	150
Specific Gravity	0.845
Viscosity @ 40°C, cSt @100°C, cSt	150 19.1
Viscosity Index	145
Flash Point, °F (°C)	515 (270)
Fire Point, °F (°C)	580 (304)
Pour Point, °F (°C)	-49 (-45)
FZG Gear Test	12+ Pass
NSF Registered (154748)	H1



Nonfood Compounds  
Program Listed: H1  
Registration