

PRODUCT DATA SHEET



PNEUMA-TOOL Food Grade 22

FG
FOOD GRADE

Mineral Oil Based Air Tool and Air Line Lubricant

PNEUMA-TOOL Food Grade-22 is a premium white oil, specially formulated for use with air lines and air tools in bakeries, meat & poultry processing or other environments where a food grade lubricant is required.

PNEUMA-TOOLS Food Grade-22 begins with a highly refined mineral oil, formulated with additives that give it excellent oxidization and corrosion resistance, low temperature fluidity, and superior wear resistance. PNEUMA-TOOL Food Grade also contains an emulsifier that ensures superior performance and protection in high moisture conditions.

PNEUMA-TOOL Food Grade meets FDA requirements for use where incidental contact with food is possible and is NSF Registered, H1.



Properties / Characteristics	PNEUMA-TOOL Food Grade 22
ISO Grade	22
Specific Gravity	0.860
Viscosity @ 40°C, cSt @100°C, cSt	22.3 4.3
Viscosity Index	96
Flash Point, °F (°C)	405 (207)
Fire Point, °F (°C)	440 (227)
Pour Point, °F (°C)	5 (-15)
Rust Test	Pass
Copper Corrosion Test	1A
Four Ball Wear Test (mm)	0.54
Foaming Test	0/0
NSF Registered (153636)	H1