PRODUCT DATA SHEET



SYN-CONVEYOR Food Grade 46



Synthetic Cooler, Conveyor, Chain & Circulating Lubricant

is a premium full synthetic (PAO) lubricant designed to meet a wide variety of food production demands.

SYN-CONVEYOR Food Grade 46 is NSF Registered and H1 designated, meeting FDA 21 CFR 178.3570 for use in applications where incidental contact with food is possible.

SYN-CONVEYOR Food Grade 46 is well suited for use in bakeries and other food production environments where its:

- Excellent compatibility with seal materials including Viton, Neoprene, PVC, Rubber, etc.
- extremely low evaporation loss
- excellent anti-wear characteristics
- thermo-oxidative stability
- reduced tendency for buildup and deposit formation
- suitability for use in automated lubrication systems

make it an excellent choice for use in:

- Hydraulic Systems
- Conveyors
- Canning Lines
- Meat Processing & Food Production

Properties / Characteristics	SYN-CONVEYOR Food Grade 46
ISO Grade	46
Viscosity @ 40°C, cSt @100°C, cSt	46.0 7.9
Viscosity Index	127
Specific Gravity	0.83
Flash Point, °F (°C)	500 (260)
Pour Point, °F (°C)	-42 (-41)
Copper Corrosion Test	1B
Foaming Sequence I, II, III	Nil
NSF Registration (#156777)	H1

