



SYN-TOOL NFG—32

SYN-TOOL NFG-32 synthetic air line lubricant is formulated from the highest quality, wax-free, synthesized hydrocarbon fluids available and fortified with an additive system designed for the most demanding air tool applications. The unique properties inherent in this synthetic air line lubricant make it especially effective in counteracting the moisture present in all compressed air. The extremely low vapor pressure and excellent metal wetting property of SYN-TOOL NFG-32 oil's allow it to outperform regular lubricants and significantly reduce lubricant consumption. Here are a few of the benefits of using SYN-TOOL NFG-32:

- Lower vapor pressure and unique metal wetting properties reduce lubricant consumption.
- Moisture in the compressed air is emulsified to protect metal surfaces and prevent rust.
- Enhanced extreme pressure properties protect tools from seizure and wear and provide good adherence to wet working surfaces.
- Elimination of lubricant oxidation prevents lost time due to gumming and varnishing.
- Proper atomization for good lubrication and control of fogging.
- Extremely good low temperature properties to protect equipment in adverse weather conditions.

SYN-TOOL NFG	32
ISO Grade	32
Viscosity @40°C, cSt @100°C, cSt	30.6 5.80
Viscosity Index	134
Flash Point, °F (°C)	450 (232)
Pour Point, °F (°C)	-55 (-48)